E/ECE/324
E/ECE/TRANS/505 } Rev.1/Add.29/Rev.1/Amend.3

12 June 1997

AGREEMENT

CONCERNING THE ADOPTION OF UNIFORM TECHNICAL PRESCRIPTIONS FOR WHEELED VEHICLES, EQUIPMENT AND PARTS WHICH CAN BE FITTED AND/OR BE USED ON WHEELED VEHICLES AND THE CONDITIONS FOR RECIPROCAL RECOGNITION OF APPROVALS GRANTED ON THE BASIS OF THESE PRESCRIPTIONS */

(Revision 2, including the amendments entered into force on 16 October 1995)

Addendum 29: Regulation No. 30

Revision 1 - Amendment 3

Incorporating:
Supplement 6 to the 02 series of amendments - Date of entry into force: 26 December 1996
Supplement 7 to the 02 series of amendments - Date of entry into force: 5 March 1997

UNIFORM PROVISIONS CONCERNING THE APPROVAL OF PNEUMATIC TYRES FOR MOTOR VEHICLES AND THEIR TRAILERS

UNITED NATIONS

---

*/ Former title of the Agreement:

Agreement Concerning the Adoption of Uniform Conditions of Approval and Reciprocal Recognition of Approval for Motor Vehicle Equipment and Parts, done at Geneva on 20 March 1958.

GE.97-21667

Paragraph 3.1.9., amend to read (including a new footnote */):

"3.1.9. The date of manufacture in the form of a group of four digits, the first two showing the week and the last two the year of manufacture. However, this marking, ... into force of this Regulation. */

---

*/ Before 1 January 2000, the date of manufacture may be indicated by a group of three digits, the first two showing the week and the last one the year of manufacture."

Insert a new paragraph 3.1.10., to read:

"3.1.10. An identification of the tyre to rim fitment configuration when it differs from the standard configuration."

Paragraph 4.1.4., amend to read (in conformity with paragraph 2.1.4.):

"4.1.4. Structure: diagonal (bias ply), bias belted or radial;"

Paragraph 4.2., amend to read:

"The application for approval shall be accompanied (all in triplicate) by a sketch, or a representative photograph, which identify the tyre tread pattern and a sketch of the envelope of the inflated tyre mounted on the measuring rim showing the relevant dimensions (see paragraphs 6.1.1. and 6.1.2.) of the type submitted for approval. It shall also be accompanied either by the test report issued by the approved Test Laboratory or by one or two samples of the tyre type, at the discretion of the competent authority. Drawings or photographs of the side wall and tread of the tyre shall be submitted once production has been established, no later than one year after the date of issue of the type approval."

Annex 3, in the example of the marking shown, replace the figure "253" by "2503", and in the explanatory text below, amend the words
"manufactured in the twenty-fifth week of the year 1973"
to read "manufactured during the twenty-fifth week of the year 2003."

Annex 5, insert a new Table IV, to read:

"Table IV: 45 Series - Radial on TR Metric 5° Rims

Size	Measuring rim width	Overall diameter	Tyre section width
280/45 R 415	240	661	281

"